

eS_{pro}45

eS_{pro}70

CHOOSE THE VEHICLE BEST SUITED TO YOUR BUSINESS.



Colours and graphics can be customised to satisfy the specific requirements of your business.



www.askollelectric.com

| Traction | | | | |
|--------------|--|-----------|--|--|
| | eSpro45 | eSpro70 | | |
| Motor | Askoll brushless permanent magnet electric motor | | | |
| Power | 2.200 W * | 2.700 W * | | |
| Max speed | 45 km/h * | 66 km/h * | | |
| Max torque | 130 Nm (to the wheel) | | | |
| Regeneration | Yes | | | |
| Transmission | Pulley w/ toothed timing belt | | | |

| Removable battery | | | | |
|-----------------------------------|-----------------|-----------------|--|--|
| | eSpro45 | eSpro70 | | |
| Туре | Lithium-ion | | | |
| Capacity (2 packs) | max. 2.090 Wh | max. 2.820 Wh | | |
| Voltage | 54 V | | | |
| Weight (for each battery pack) | 7,6 kg | 8 kg | | |
| Charging time 2 batteries | 5,5 hours (80%) | 7,5 hours (80%) | | |
| Range (up to) | 71 km * | 96 km * | | |

| General information | | | | |
|------------------------------|--|--|--|--|
| | eSpro45 | eSpro70 | | |
| Front Lighting | Halogen | LED | | |
| Back Lighting | LED | | | |
| Direction indicator lighting | LED built into the body | | | |
| Colours available | Red / Black / White | | | |
| Customisations | Colours and grap for specific requi | Colours and graphics can be customised for specific requirements | | |

| Cycle parts | | |
|--|--------------------------------------|--|
| | eSpro45 | eSpro70 |
| Front suspension | Hydraulic telescopic fork | |
| Back suspension | Hydraulic shock absorber | |
| Brakes | Front: hydraulic disk Ø 190 mm | Service brake: CBS Combined Braking System Front: hydraulic disk Ø 220 mm Back: drum Ø 140 mm |
| | Back: drum Ø 140 mm | Emergency brake: Front: hydraulic disk Ø 220 mm |
| Front tyre | 80 / 80 - 16" | |
| Back tyre | 90 / 80 - 16" | |
| Wheelbase | 1.245 mm | |
| Seat height | 760 mm | |
| Weight in running order | 67 kg * | 70 kg * |
| Max. weight (vehicle + driver + additional load) | 235 kg | 245 kg |

Technical specifications may be subject to change without prior notice.